

verae-zapier-middleware/debug/trace-context

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/debug/trace-context.js

****Lines:**** 40

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

traceStorage, generateTraceId, getTraceId, getTraceContext

Types / interfaces / classes

None extracted.

Functions

· Name ·	Parameters ·	Param types (JSDoc) ·	Returns ·	Calls (same file / helpers) ·
· ----- ·	· ----- ·	· ----- ·	· ----- ·	· ----- ·
· generateTraceId ·	· (none) ·	· — ·	· string ·	· see Call graph ·
· getTraceId ·	· (none) ·	· — ·	· string · null ·	· see Call graph ·
· getTraceContext ·	· (none) ·	· — ·	· TraceContext · null ·	· see Call graph ·

What it imports / requires

- node:async_hooks
- node:crypto

Call graph (identifiers invoked)

context, id, generateTraceId, randomBytes, toString, getTraceId, getStore, getTraceContext

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.