

verae-zapier-middleware/debug/trace

****Package:**** verae-zapier-middleware
****Source:**** packages/verae-zapier-middleware/src/debug/trace.js
****Lines:**** 96

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

withTrace, traceMiddleware

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·
· ----- · ----- · ----- · ----- · ----- ·
· withTrace · options, fn · options: object · (() => T · Promise<T>), options.tracelId: string, options.span: string, fn: () => T · Promise<T> · T · Promise<T> — Return value of fn. · see Call graph ·
· traceMiddleware · req, res, next · req: import('express').Request, res: import('express').Response, next: import('express').NextFunction · void · see Call graph ·

Methods (class / object)

· Name · Parameters ·
· ----- · ----- ·
· withTrace · { tracelId, span: \${req.method} \${req.path} }, (·

What it imports / requires

- ./logger.js
- ./trace-context.js

Call graph (identifiers invoked)

createDebugger, id, span, withTrace, async, getTraceId, getStore, generateTraceId, run, debug, callback, then, import, traceMiddleware, trim, setHeader, next

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.