

verae-zapier-middleware/store/db

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/store/db.js

****Lines:**** 115

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

emptyStore, loadStore, getStore, setStoreForTests, persist, reloadStore

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·
· ----- · ----- · ----- · ----- · ----- ·
· emptyStore · (none) · — · StoreShape · see Call graph ·
· loadStore · path = config.storePath · path: string · StoreShape · see Call graph ·
· getStore · (none) · — · StoreShape · see Call graph ·
· setStoreForTests · next · next: StoreShape · null · void · see Call graph ·
· persist · path = config.storePath · path: string · void · see Call graph ·
· reloadStore · path = config.storePath · path: string · StoreShape · see Call graph ·

Methods (class / object)

· Name · Parameters ·
· ----- · ----- ·
· writeFileSync · path, JSON.stringify(data, null, 2) ·

What it imports / requires

- node:fs
- node:path
- ../config.js
- ../debug/logger.js

Call graph (identifiers invoked)

store, createDebugger, emptyStore, memory, loadStore, existsSync, readFileSync, parse, isArray, debug, keys, error, getStore, setStoreForTests, persist, dirname, mkdirSync, writeFileSync, stringify, disk, reloadStore

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.