

verae-zapier-middleware/workers/jobPollerWorker

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/workers/jobPollerWorker.js

****Lines:**** 159

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

startJobPollerWorker, stopJobPollerWorker

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·

· ----- · ----- · ----- · ----- · ----- ·

· resolveVeraeToken · msg · msg: object · Promise<string> · see Call graph ·

· handleWatch · data, ctrl · data: object · unknown · see Call graph ·

· startJobPollerWorker · (none) · — · Promise<{ stop: () => Promise<void> — }> · see Call graph ·

· stopJobPollerWorker · (none) · — · Promise<void> · see Call graph ·

What it imports / requires

- ../debug/logger.js
- ../config.js
- ../nats/subjects.js
- ../nats/connection.js
- ../nats/publishers.js
- ../clients/veraeClient.js
- ../store/tenants.js

- ../debug/trace.js

Call graph (identifiers invoked)

createDebugger, polling, resolveVeraeToken, getTenant, login, handleWatch, withTrace, async, publishJobEvent, ack, getStatus, debug, nak, startJobPollerWorker, stopJobPollerWorker, connectNats, ensureStreams, consumer, add, get, info, consume, parse, string, error, abort

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express res.json(...) bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on Quote.totalCents.