

zappier/admin-users

```
**Package:** zappier
**Source:** packages/zappier/src/admin-users.ts
**Lines:** 76
```

What this module is

Implementation module in zappier. The tables below are extracted from the source (signatures + JSDoc).

Exports

AdminUser, AdminUserRepo, newAdminUserId, seedAdminUsersFromEnv, makeAdminUser, InMemoryAdminUserRepo

Types / interfaces / classes

```
· Kind · Name ·
· ----- · ----- ·
· interface · AdminUser ·
· interface · AdminUserRepo ·
· class · InMemoryAdminUserRepo ·
```

Functions

```
· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·
· ----- · ----- · ----- · ----- · ----- ·
· newAdminUserId · (none) · — · unknown · see Call graph ·
· seedAdminUsersFromEnv · (none) · — · unknown · see Call graph ·
· · _The env-backed seed accounts (preserved from the pre-table behavior)._ · . . . ·
· makeAdminUser · username: string, password: string · — · unknown · see Call graph ·
```

Methods (class / object)

```
· Name · Parameters ·
· ----- · ----- ·
· list · (none) ·
```

- findByUsername · username: string ·
- save · user: AdminUser ·
- list · (none) ·
- findByUsername · username: string ·
- save · user: AdminUser ·

What it imports / requires

- crypto
- ./accounts

Call graph (identifiers invoked)

list, findByUsername, save, newAdminUserId, randomBytes, toString, accounts, seedAdminUsersFromEnv, makeAdminUser, hashPassword, now, constructor, map, seeded, find, findIndex, push

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.