

zappier/billing/reload

```
**Package:** zappier
**Source:** packages/zappier/src/billing/reload.ts
**Lines:** 32
```

What this module is

Implementation module in zappier. The tables below are extracted from the source (signatures + JSDoc).

Exports

stripePaymentClient, hasRealStripeKey

Types / interfaces / classes

None extracted.

Functions

· Name ·	Parameters ·	Param types (JSDoc) ·	Returns ·	Calls (same file / helpers) ·
· stripePaymentClient ·	secretKey: string ·	— ·	unknown ·	see Call graph ·
· hasRealStripeKey ·	key: string \ ·	undefined ·	— ·	unknown · see Call graph ·
· _	True when the key looks usable (not empty / not the setup placeholder)._ · · · ·			

What it imports / requires

- stripe
- ../portal

Call graph (identifiers invoked)

confirms, stripePaymentClient, async, create, usable, hasRealStripeKey, startsWith

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.