

zappier/db/pricing-store

```
**Package:** zappier  
**Source:** packages/zappier/src/db/pricing-store.ts  
**Lines:** 107
```

What this module is

Implementation module in zappier. The tables below are extracted from the source (signatures + JSDoc).

Exports

SqlitePricingStore

Types / interfaces / classes

```
· Kind · Name ·  
· ----- ·  
· class · SqlitePricingStore ·
```

Functions

No top-level functions extracted.

Methods (class / object)

```
· Name · Parameters ·  
· ----- ·  
· constructor · private db: Database.Database,  
seedCard: RateCard = DEFAULT_RATE_CARD,  
seedTiers: TierConfig[] = DEFAULT_TIERS, |  
· getRateCard · (none) ·  
· getTiers · (none) ·  
· upsertEndpoint · endpointId: string, rule: PriceRule ·  
· deleteEndpoint · endpointId: string ·  
· upsertTier · tier: TierConfig ·  
· deleteTier · tierId: string ·
```

What it imports / requires

- better-sqlite3
- ../pricing

Call graph (identifiers invoked)

constructor, exec, price_endpoints, tiers, prepare, get, entries, upsertEndpoint, upsertTier, getRateCard, all, parse, getTiers, map, run, stringify, deleteEndpoint, deleteTier

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.