

verae-zapier-middleware/services/authService

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/services/authService.js

****Lines:**** 142

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

loginWithCredentials, loginWithApiKey, resolveAuthContext, validateSession

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·

· ----- · ----- · ----- · ----- · ----- ·

· loginWithCredentials · { username, password, tenant } · params: object, params.username: string, params.password: string, params.tenant: object · Promise<{ accessToken: string, expiresAt: string, tenant: object, user: object — >} · see Call graph ·

· loginWithApiKey · apiKey · apiKey: string · Promise<Awaited<ReturnType<typeof loginWithCredentials>>> · see Call graph ·

· resolveAuthContext · rawToken · rawToken: string · null · Promise<{ tenantId: string, tenant: object, veraeToken: string, authMethod: string — >} · see Call graph ·

· validateSession · rawToken · rawToken: string · Promise<object> · see Call graph ·

What it imports / requires

- ../clients/veraeClient.js
- ../store/tenants.js
- ../lib/tokens.js
- ../errors.js

- ../debug/logger.js

Call graph (identifiers invoked)

createDebugger, loginWithCredentials, debug, login, issueSessionToken, loginWithApiKey, getTenantByApiKey, resolveAuthContext, isApiKey, parseSessionToken, getTenant, parse, now, validateSession, validate

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express res.json(...) bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on Quote.totalCents.