

verae-zapier-middleware/services/webhookService

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/services/webhookService.js

****Lines:**** 71

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

subscribe, unsubscribe, deliverWebhook

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·

· ----- · ----- · ----- · ----- · ----- ·

· subscribe · ctx, { targetUrl, event } · ctx: object · unknown · see Call graph ·

· unsubscribe · ctx, { hookId, targetUrl } · ctx: object · unknown · see Call graph ·

· deliverWebhook · targetUrl, payload · targetUrl: string, payload: object · Promise<{ ok: boolean, status: number —> } · see Call graph ·

What it imports / requires

- ../store/webhooks.js
- ../debug/logger.js

Call graph (identifiers invoked)

createDebugger, subscribe, has, createWebhook, unsubscribe, deleteWebhook, deliverWebhook, debug, fetch, stringify

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.