

verae-zapier-middleware/store/tenants

```
**Package:** verae-zapier-middleware
**Source:** packages/verae-zapier-middleware/src/store/tenants.js
**Lines:** 138
```

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

getTenant, getTenantByApiKey, listTenants, upsertTenant, createTenant, resolveLimits

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·

· ----- · ----- · ----- · ----- · ----- ·

· getTenant · tenantId · tenantId: string · Tenant · null · see Call graph ·

· getTenantByApiKey · apiKey · apiKey: string · Tenant · null · see Call graph ·

· listTenants · (none) · — · Tenant[] · see Call graph ·

· upsertTenant · tenant · tenant: Tenant · Tenant · see Call graph ·

· createTenant · {

id,

name,

plan = 'free',

veraeUsername,

veraePassword,

contract = null,

apiKey = generateApiKey(| params: object, params.id: string, params.name: string, params.plan: string,
params.veraeUsername: string, params.veraePassword: string, params.contract: object|null, params.apiKey:
string, params.metadata: object | { tenant: Tenant, apiKey: string — } | see Call graph |

· resolveLimits · tenant · tenant: Tenant · {

- * timestamps: number|null,
- * verifications: number|null,
- * batch: boolean,
- * batchMaxItems: number|null,
- * requestsPerMinute: number,
- * allowOverage: boolean,
- * overageRates: object
- * — } | see Call graph |

Methods (class / object)

· Name · Parameters ·

· ----- ·

· persist · (none) ·

· persist · (none) ·

What it imports / requires

- ./db.js
- ../lib/tokens.js
- ../config.js
- ../debug/logger.js

Call graph (identifiers invoked)

createDebugger, getTenant, getStore, getTenantByApiKey, listTenants, values, upsertTenant, persist, debug, createTenant, generateApiKey, toISOString, info, tenant, resolveLimits

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express res.json(...) bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on Quote.totalCents.