

verae-zapier-middleware/store/usage

****Package:**** verae-zapier-middleware

****Source:**** packages/verae-zapier-middleware/src/store/usage.js

****Lines:**** 103

What this module is

Implementation module in verae-zapier-middleware. The tables below are extracted from the source (signatures + JSDoc).

Exports

getUsage, getUsageSummary, incrementUsage

Types / interfaces / classes

None extracted.

Functions

· Name · Parameters · Param types (JSDoc) · Returns · Calls (same file / helpers) ·
· ----- · ----- · ----- · ----- · ----- ·
· currentPeriod · (none) · — · string — YYYY-MM period key · see Call graph ·
· emptyUsage · tenantId · tenantId: string · { period: string, timestamps: number, verifications: number, statusChecks: number, batchTimestamps: number, overage: object — } · see Call graph ·
· getUsage · tenantId · tenantId: string · ReturnType<typeof emptyUsage> · see Call graph ·
· getUsageSummary · tenantId · tenantId: string · object · see Call graph ·
· incrementUsage · tenantId, metric, amount = 1 · tenantId: string, metric: string, amount: number · void · see Call graph ·

Methods (class / object)

· Name · Parameters ·
· ----- · ----- ·
· getStore · (none) ·
· persist · (none) ·

What it imports / requires

- ./db.js
- ./tenants.js
- ../debug/logger.js

Call graph (identifiers invoked)

createDebugger, currentPeriod, getUTCFullYear, getUTCMonth, padStart, emptyUsage, getUsage, getStore, getUsageSummary, getTenant, resolveLimits, incrementUsage, startsWith, slice, persist, debug

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express res.json(...) bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on Quote.totalCents.