

zappier/db/billing-repo

```
**Package:** zappier  
**Source:** packages/zappier/src/db/billing-repo.ts  
**Lines:** 69
```

What this module is

Implementation module in zappier. The tables below are extracted from the source (signatures + JSDoc).

Exports

BillingReportRepo, JobLockRepo, SqliteBillingReportRepo

Types / interfaces / classes

```
· Kind · Name ·  
· ----- · ----- ·  
· interface · BillingReportRepo ·  
· interface · JobLockRepo ·  
· class · SqliteBillingReportRepo ·
```

Functions

No top-level functions extracted.

Methods (class / object)

```
· Name · Parameters ·  
· ----- · ----- ·  
· getReportedCents · customerId: string, period: string ·  
· upsertReportedCents · customerId: string, period: string, cumulativeCents: number ·  
· tryAcquireLock · name: string, ttlMs: number ·  
· releaseLock · name: string ·  
· constructor · private db: Database.Database,  
private now: ( |  
· getReportedCents · customerId: string, period: string ·
```

- upsertReportedCents · customerId: string, period: string, cumulativeCents: number ·
- tryAcquireLock · name: string, ttlMs: number ·
- releaseLock · name: string ·

What it imports / requires

- better-sqlite3

Call graph (identifiers invoked)

getReportedCents, upsertReportedCents, tryAcquireLock, releaseLock, constructor, exec, billing_reports, job_locks, prepare, get, run, now

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express res.json(...) bodies (see route docs).
- Zapier perform functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on Quote.totalCents.